

Cat. No.	SIL60
Notes	

Section 10309 - Manufactured Electric Fireplaces

PART 1 GENERAL

1.1 SECTION INCLUDES

- Manufactured electric fireplaces.
- B. Accessories.

1.2 RELATED SECTIONS

A. Section 06100 - Rough Carpentry: Wood framed rough opening and enclosure.

1.3 REFERENCES

- A. UL 2021
- B. CSA C22.2 No. 46

1.4 SUBMITTALS

- A. Submit under provisions of Section 01300.
- B. Product Data: Manufacturer's data sheets on each product to be used, including:
 - 1. Preparation instructions and recommendations.
 - 2. Storage and handling requirements and recommendations.
 - Installation methods.
- C. Manufacturer's Certificates: Certify products meet or exceed specified requirements.
- D. Manufacturer's warranty.

1.5 DELIVERY, STORAGE, AND HANDLING

- A. Store products in manufacturer's unopened packaging until ready for installation.
- B. Protect materials from exposure to moisture. Do not deliver until after wet work is complete and dry.

1.6 WARRANTY

A. Provide the manufacturers 1 year limited warranty on electrical components.

PART 2 PRODUCTS

2.1 ACCEPTABLE MANUFACTURERS

- A. Pre-fabricated Electric Fireplace:
 - 1. Base: Dimplex Electric Fireplace

Glen Dimplex Americas

1367 Industrial Road

Cambridge ON N3H 4C3

1-888-DIMPLEX

www.dimplex.com



Cat. No.	SIL60
Notes	

Section 10309 – Manufactured Electric Fireplaces

- 2. Substitutions not permitted
- Requests for substitutions will be considered in accordance with provisions of Section 01600.

2.2 ELECTRIC FIREPLACES

- A. General:
 - 1. Provide all components and accessories required for a complete, functional unit.
 - 2. UL or CSA listed.
- B. Pre-fabricated Electric Fireplace:
 - 1. Base Product:
 - a) Dimplex Linear Electric Fireplace
 - b) Model Number: SIL60
 - 2. Description: 60" wall-mounted linear electric fireplace
 - 3. Dimensions:
 - a) Width: 60" / 1524mm
 - b) Height: 19-1/2" / 495.3mm
 - c) Depth: 5" / 127mm
 - 4. Framing Dimensions:
 - a) Width: 52-5/8" / 1336.5mm
 - b) Height: 18-1/2" / 469.9mm
 - c) Depth: 6-1/2" / 165.1mm
 - 5. Electrical:
 - a) Volts: 120
 - b) Watts: 1,400
 - c) BTUs: 5000
 - d) Amps: 12.5
 - 6. Venting: Non-venting
 - 7. Operation: Flame only, flame and heat
 - 8. Heating: Louver-less, fan-forced circulation
 - 9. Liner: Steel
 - 10. Standard features:
 - a) Flame/ember bed on/off, range of color themes
 - b) LED flame technology
 - c) Interchangeable Media Bed acrylic crystal, logs, or pebbles
 - d) Built-in capacitive touch controls
 - e) Built-in Timer Set for up to 8 hours.
 - f) On-demand ceramic heater
 - g) Easy installation plug into any standard household outlet
 - 1. Control options:
 - a) Multi-function remote control
 - b) Built-in Capacitive controls



Cat. No.	SIL60
Notes	

Section 10309 – Manufactured Electric Fireplaces

PART 2 EXECUTION

2.1 INSPECTION

- A. Do not begin installation until substrates have been properly prepared.
- B. If substrate preparation is the responsibility of another installer, notify Architect of unsatisfactory preparation before proceeding.
- C. Verify proper power supply and fuel source are available.

2.2 PREPARATION

- A. Clean surfaces thoroughly prior to installation.
- B. Prepare surfaces using the methods recommended by the manufacturer for achieving the best result for the substrate under the project conditions.

2.3 INSTALLATION

- A. Install in accordance with manufacturer's instructions and requirements of authorities having jurisdiction.
- B. Use manufacturer's guidelines for minimum clearances to combustibles, walls, and finishes.
- C. Anchor all components firmly in position for long life under hard use.
- D. Upon completion of installation, visually inspect all exposed surfaces. Touch up scratches and abrasions with touch up paint recommended by the manufacturer; make imperfections invisible to the unaided eye from a distance of 5 feet (1.5 m).

2.4 PROTECTION

- A. Protect installed products until completion of project.
- B. Touch-up, repair or replace damaged products before Substantial Completion.

END OF SECTION