

Cat. No.

Notes

# Section 10309 – Manufactured Electric Fireplaces

### PART 1 GENERAL

### 1.1 SECTION INCLUDES

- A. Manufactured electric fireplaces.
- B. Accessories.

### 1.2 RELATED SECTIONS

A. Section 06100 - Rough Carpentry: Wood framed rough opening and enclosure.

### 1.3 REFERENCES

- A. UL 60065
- B. CSA C22.2 No. 60065-3
- C. IEC60065

### 1.4 SUBMITTALS

- A. Submit under provisions of Section 01300.
- B. Product Data: Manufacturer's data sheets on each product to be used, including:
  - 1. Preparation instructions and recommendations.
    - 2. Storage and handling requirements and recommendations.
  - 3. Installation methods.
- C. Manufacturer's Certificates: Certify products meet or exceed specified requirements.
- D. Manufacturer's warranty.

### 1.5 DELIVERY, STORAGE, AND HANDLING

- A. Store products in manufacturer's unopened packaging until ready for installation.
- B. Protect materials from exposure to moisture. Do not deliver until after wet work is complete and dry.

#### 1.6 WARRANTY

A. Provide the manufacturers 2-year limited warranty on electrical components.

## PART 2 PRODUCTS

#### 2.1 ACCEPTABLE MANUFACTURERS

- A. Pre-fabricated Electric Fireplace:
  - Base: Dimplex Electric Fireplace Dimplex North America 1367 Industrial Road Cambridge ON N1R 7G8 1-888-DIMPLEX www.dimplex.com archdesign@dimplex.com



Cat. No.

Notes

## Section 10309 – Manufactured Electric Fireplaces

- 2. Substitutions not permitted
- 3. Requests for substitutions will be considered in accordance with provisions of Section 01600.

## 2.2 ELECTRIC FIREPLACES

- A. General:
  - 1. Provide all components and accessories required for a complete, functional unit.
  - 2. UL or CSA listed.
- B. Pre-fabricated Electric Fireplace:
  - 1. Base Product:
    - a) Dimplex Electric Fireplace
    - b) Model Number: VF5452L
  - 2. Description: 54" High definition virtual Electric Fireplace with wood fire sound effects
  - 3. Dimensions:
    - a) Width: 54-3/8" / 1380mm
    - b) Height: 17-3/4" / 450mm
    - c) Depth: 13-1/2" / 343mm
  - 4. Framing Dimensions:
    - a) Width: 55-1/4" / 1404mm
    - b) Height: 18-5/8" / 474mm
    - c) Depth: 13-5/8" / 345mm
  - 5. Electrical:
    - a) Volts: 120V
    - b) Watts: 64
    - c) Amps: 0.53
    - d) BTU: 218.4
  - 6. Venting: Non-venting
  - 7. Operation: Flame only (no heat)
  - 8. Heating: N/A
  - 9. Standard features:
    - a) Extremely low energy LEDs in the fuel bed and lighting
    - b) Three dimensional flame technology
    - c) Two sets of inner glow LED logs (visible and reflected) that create patented 3D illusion of virtual flames
    - d) Wood fire sound effects
    - e) Actual flame footage rendered in high definition
    - f) Direct wire 120
    - g) Components serviceable through viewing aperture
  - 10. Control options:
    - a) Built-in on/off and volume control switches
    - b) Multi-function remote control, with sound effect volume control
    - c) Wall switch remote control kit



Cat. No.

Notes

# Section 10309 – Manufactured Electric Fireplaces

## PART 3 EXECUTION

### 3.1 INSPECTION

- A. Do not begin installation until substrates have been properly prepared.
- B. If substrate preparation is the responsibility of another installer, notify Architect of unsatisfactory preparation before proceeding.
- C. Verify proper power supply and fuel source are available.

### 3.2 PREPARATION

- A. Clean surfaces thoroughly prior to installation.
- B. Prepare surfaces using the methods recommended by the manufacturer for achieving the best result for the substrate under the project conditions.

### 3.3 INSTALLATION

- A. Install in accordance with manufacturer's instructions and requirements of authorities having jurisdiction.
- B. Use manufacturer's guidelines for minimum clearances to combustibles, walls, and finishes.
- C. Anchor all components firmly in position for long life under hard use.
- D. Upon completion of installation, visually inspect all exposed surfaces. Touch up scratches and abrasions with touch up paint recommended by the manufacturer; make imperfections invisible to the unaided eye from a distance of 5 feet (1.5 m).

### 3.4 PROTECTION

- A. Protect installed products until completion of project.
- B. Touch-up, repair or replace damaged products before Substantial Completion.

### END OF SECTION