

COMMERCIAL FAN-FORCED HEATER

Solutions for maintaining comfort in areas subject to cold drafts, such as vestibules, stairwells, etc.

BENEFITS

- Quick-response, high-output, fan-forced heater
- Automatic fan delay utilizes residual heat when unit cycles off
- Recessed or surface mounted options, in ceilings or walls, available for 240/208 volt installations
- Includes built-in, double-pole thermostat
- Access door can be locked for tamperproof applications
- 20 gauge steel grill provides maximum durability



APPLICATIONS

Vestibules | Entranceways | Stairwells | Kiosks

SPECIFICATIONS


Voltage	208V, 240/208V
Wattage	Sizes ranging from 1500W to 4800W
Color	White
Finish	Powder coating resists fading and abrasion
Construction	20 gauge steel front panel
Heating Element	Fully-enclosed steel sheath element with spiral fins to provide excellent heat transfer
Warranty	1-year warranty on complete unit

ORDERING GUIDE

Part	Cat. No.	Watts	BTU	Volts	Phase	CFM	Weight (kg/lbs.)
52982	RFI815D31W	1500 / 1125	5118 / 3840	240 / 208	1	160	12.7 / 28
52983	RFI820D31W	2000 / 1500	6824 / 5118	240 / 208	1	160	12.7 / 28
52984	RFI830D31W	3000 / 2250	10236 / 7680	240 / 208	1	160	12.7 / 28
53136	RFI840D21W	4000	13648	208	1	160	12.7 / 28
52985	RFI840D31W	4000 / 3000	13648 / 10236	240 / 208	1	160	12.7 / 28
53138	RFI848D31W	4800 / 3600	16378 / 12283	240 / 208	1	160	12.7 / 28

ACCESSORIES (field installed)

Part	Cat. No.	Description
50678	RFP8DW	Surface mount box for RFI (white) (425mm x 546mm x 97mm) 16.8" x 21.5" x 3.8"
50360	RFITF	T-Bar ceiling frame for RFI series (white)
50672	RFIFPW	RFI Front panel kit (white)



RFP8DW Surface mount box



RFITF T-bar Ceiling Mount Trim (white only)



DIMENSIONS

